




The Patent Office
Concept House
Cardiff Road
Newport
Southewales OCT 2003
NP10 800
WIPO PCT

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed ANSHUME .

Dated 5 August 2003

PRIORITY DOCUMENT

SUBMITTED OR TRANSMITTED IN COMPLIANCE WITH RULE 17.1(a) OR (b)

Patents Form 1/77 Patents 1977 (Rule i 29JUL02 E736519-2 D02624 26 JUL 2002 P01/7700 0.00-0217385.4 Request for grant of a patent The Patent Office (See the notes on the back of this forth Toward also get an Cardiff Road explanatory leaflet from the Patent Office to help you fill in Newport this form) South Wales NP9 1RH Your reference JC/SPY 0217385.4 2. Patent application number · 26 IUL 2002 (The Patent Office will fill in this part) 3. Full name, address and postcode of the or of each applicant (underline all surnames) GOPAK LTD. Range Road, Hythe, 8433422001 Patents ADP number (if you know it) Kent, CT21 6HG. If the applicant is a corporate body, give the country/state of its incorporation GB Title of the invention Stanchion Support Name of your agent (if you have one) "Address for service" in the United Kingdom J.C. BRIDGE-BUTLER to which all correspondence should be sent (including the postcode) G.F. REDFERN & CO. 7 Staple Inn, Holborn, London WC1V 7QF 1976381001 Patents ADP number (if you know it) If you are declaring priority from one or more Country Priority application number Date of filing earlier patent applications, give the country (if you know it) (day / month / year) and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number 7. If this application is divided or otherwise Number of earlier application Date of filing derived from an earlier UK application, (day / month / year) give the number and the filing date of the earlier application 8. Is a statement of inventorship and of right

Yes

to grant of a patent required in support of

b) there is an inventor who is not named as an

any named applicant is a corporate body.

a) any applicant named in part 3 is not an inventor, or

this request? (Answer Yes' if:

applicant, or

See note (d))

Patente Ban 1 /77

Patents Form 1/77 9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document Continuation sheets of this form Description 5 Claim (s) Abstract 1 + 1 Drawing(s) 10. If you are also filing any of the following, state how many against each item. Priority documents Translations of priority documents Statement of inventorship and right to grant of a patent (Patents Form 7/77) Request for preliminary examination and search (Patents Form 9/77) Request for substantive examination (Patents Form 10/77) Any other documents (please specify) I/We request the grant of a patent on the basis of this application. 11. Date

12. Name and daytime telephone number of person to contact in the United Kingdom BRIDGE-BUTLER

020 7242 7680

26 July 2002

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505. Notes
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form...
- d) If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- e) Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

Stanchion support

This invention relates to a support means for a stanchion, which is particularly, but not exclusively in the form of a table leg.

Collapsible legs for use with folding tables and chairs and the like are well known. The upper ends of the legs can be attached in a hinged arrangement to the underside of the body of the item of furniture, so that they can be folded up underneath the body for storage. There are many known types of folding mechanisms which utilise a variation of designs.

The chief aims of any folding mechanism are twofold. Firstly, the mechanism must be able to adequately support the leg when it is extended, so that the table or other article, will not collapse during use. Secondly, the mechanism must facilitate ease of use, so that the leg can be readily extended and collapsed.

One design which has proved successful comprises a pair of legs constructed from a single U-shaped component, in which the transverse interconnecting section is attached in a hinged arrangement to the underside of the table. The legs are provided with a support element which is substantially similar in size and shape to the legs component, and which is disposed alongside the legs. The two components are rigidly attached together at their outer ends in such a way that the two adjacent transverse interconnecting sections are resiliently biased together, but can be pulled apart.

When the legs are unfolded the interconnecting section of the support element is pulled away from the legs and placed in sockets provided on the underside of the table. With this arrangement the biasing together of the components holds the support element in the sockets. When the table needs to be folded up for storage, the support element can be removed from the sockets by hand, and the two components can be folded flat against the underside of the table top.

The present invention is intended to provide an improved version of the above mechanism.

According to the present invention a sliding pivot means for a support element which is used with a stanchion which is hinged to the item with which it is used and from which it can be unfolded, in which one end of the support element is rigidly attached to the stanchion and the opposite end is provided with a substantially transverse portion extending therefrom, comprises a slide, a sleeve provided with a slide pin extending in substantially the same plane as the sleeve, and a socket substantially parallel with said transverse portion, and in which the sleeve is located on the transverse portion, and the pin is located in the slide, the sleeve being adapted to rotate about the transverse portion, and the pin to rotate in the slide, the pin moving along the slide when the stanchion is rotated about its hinge, and the socket being adapted to receive the transverse portion when the stanchion is in a fully unfolded position.

Preferably the slide is curved to follow the path of the transverse portion of the support element as the stanchion is rotated about its hinge.

In one construction the socket is provided in between the underside of the item and the slide. With this arrangement the slid pin reaches the end of the slide, and the transverse portion and the sleeve rotate around the end of the slide, and into the socket.

In a preferred embodiment the item is an item of furniture. The furniture can be a table, and the stanchion can be a table leg. Further, the table leg can be part of a U-shaped two-leg component, the transverse interconnecting portion of which is hinged to the underside of the table. The support element can be substantially the same shape, and can be disposed along side the legs. The two components can be fixed together at their outer ends, in such a way that the two interconnecting portions are resiliently biased together, but can be pulled apart.

The legs and the support element can be tubular in shape, and can be constructed from any suitable material, for example wood or metal, for example steel.

The invention also includes an item provided with a sliding pivot means for a support element to be used with a stanchion which is hinged to the item, as described above.

The invention can be performed in various ways, but one embodiment will now be described by way of example and with reference to the accompanying drawings, in which:

Figure 1 is a perspective view of a sliding pivot means for a support element according to the present invention; and,

Figure 2 is a perspective view of the sliding pivot means as shown in Figure 1, in a different configuration.

As shown in Figure 1 a table 1 is provided with a cylindrical leg 2 which is hinged to a table support spar 3 by means of a circular aperture 4. The leg 2 is provided with a support element 5, the outer end of which 5a is rigidly attached to the outer end of the leg 2a (as shown in Figure 2), so that there is a V shaped configuration between the leg 2 and the element 5. The inner end 6 of the element 5 is provided with a substantially transverse portion 7 extending therefrom.

The support element 5 is provided with a sliding pivot 8 comprising a slide 9, a sleeve 10 provided with a slide pin 11 extending in the same plane as the sleeve 10 and a socket 12. The sleeve 10 is disposed around the transverse portion 7, and the pin 11 is disposed in the slide 9. The sleeve 10 can rotate about the transverse portion 7, and the pin 11 can rotate on its own axis in the slide 9.

The pin 11 is adapted to move along the slide 9 when the leg 2 is rotated about its hinge 4, and the socket 12 is adapted to receive the transverse portion 7 when the leg 2 is in the fully unfolded position.

The leg 2 and the support element 5 are parts of substantially U-shaped leg pair and support element components. An opposite sliding pivot arrangement is provided at the opposite edge of the table 1.

As shown in Figure 1 the leg 2 is in the folded position, disposed adjacent to the underside 13 of the table 1. The pin 11 is disposed at the inner end 14 of the slide 9, and the pin 11 is in a rotational position to allow the sleeve 10 and the transverse portion 7 within it to be disposed adjacent to the transverse portion 15 of the leg 2.


As shown in Figure 2 the leg 2 is in the unfolded position. The pin 11 has been moved through the slide 9, and the pin 11 and the sleeve 10 have been rotated in a clockwise direction, to allow the transverse portion 7 to be disposed within the socket 12. The transverse portion 7 has been pulled apart from the leg 2 to allow it to be moved about the end 16 of the slide 9. The inner ends of the leg 2 and the support element 5 are resiliently biased together due to their outer ends 2a and 5a being rigidly attached together. As a result the transverse portion 7 is held in the socket 12 and the leg 2 is safely held in position.

To restore the leg 2 to the folded position the transverse portion 7 must be pulled from the socket 12 by hand, and the pin 11 must be moved and rotated back through the slide 9, in a reverse of the process described above.

Thus a table provided with a U-shaped legs component and a support element which is substantially similar in size and shape and in which the outer ends of the legs and the support elements are fixed together, is provided with a novel folding and supporting system which adequately supports the leg, and can be readily used.

7

The system is also provided with a small number of simple moving parts which are easy to construct. Further, the transverse portions of the legs and the support elements cannot be pulled too far apart due to the support element being held in a slide. This increases the lifespan of the leg.





THE PATENT OFFICE
06 AUG 2003

Received in Patents International Unit